

## المواصفات الفنية

## **TECHNICAL SPECIFICATION**

## عطاء رقم BID NO. NWD-TC-2025-T-50-06

No	Otro	IIa:	Description
No.	Qty.	Uoi.	Description.
1	2	EA	Ken-worth <b>963S</b> heavy duty 6 X 6 oil field Truck complete, that can operate in all desert conditions in rough terrain, soft sand, extreme payloads, in dusty environment and high and low temperatures ranging from -5 to +55 deg. complete with the following specifications.
			Complete with the following.
			Complete with the following.  First option Cat C15 engine, / Second option Cummins ISX-600 HP suitable for desert environment and equipped with all accessories required for desert conditions as specified above.  High supply air compressor.  Dual, 16-inch Donaclone "Two Stage" Air Cleaners.  Export Type Fan Hub with Nylon Fan.  High Cooling Capacity, for high ambient temperature operations  Silicone Coolant Hoses with Stainless Steel Clamps.  Dual, Vertical, Cab-Mounted Exhausts with Stainless Steel Heat Shield & Spark Arrestor  Spin-On Coolant Filter.  DAVCO "Fuel Pro" Fuel Filter / Water Separator.  Full Flow Oil Filter.  Chassis Electric Power System is 12-volts Ampere Alternator  Four (4) Heavy-Duty 12-volt Grp-31 Threaded Post, Batteries with a 4,600-CCA rating.  12-volt Electric Starter  Battery Disconnect Switches Mounted on the Battery Box  Dana H8820 Transmission suitable for high GCW operations  High Capacity, Transmission Oil Cooler / Heat Exchanger.  Heavy Duty Drivelines.  Planetary Hub Reduction front axle, with Brakes and Dust shields  Front "Slipper Type" Springs with Radius Rods  Dual, Heavy-Duty Sheppard model 592 Power Steering Gears  Planetary Hub Reduction, Dual Rear Axles
			Dual Spring Brakes     WARD Committee Com
			KWRB Steel Beam Suspension with 75- Kenworth inch Axle Spacing

- Sand Champion 29.5 X 25 Rib-Tread Tires with tubes and 2 spares
- OTR Steel Wheels for 29.5 X 25 Tires and 2-spare
- Hydraulic Jack with 27-ton (30 US ton) Capacity and Wheel Nut Lug Wrench
- 11-5/8-inch X 3/8-inch Heat Treated (110,000 PSI Yield Strength) Steel Frame Rails
- Full Length Frame Insert for Main Frame Rail
- 10-5/8-inch X 3-1/2-inch X 5/16 inch "Stacked" Top Frame Rail
- Heavy Duty, Steel Bumper with Radiator Guard and Canter Mounted Steel Tow Pin
- Two (2) 1,040 litre (275 US Gallon) each Steel Fuel Tanks with sediment traps
- Fuel Tanks located One Left Side and One Right Side Back of Cab with Safety Guards
- Steel battery Box with Aluminium Diamond Plate Cover mounted under cab on left side.
- Toolbox with aluminium Diamond Plate Cover mounted under cab on right hand side.
- Extended Steps with Flexible Brackets for Cab Access LH and RH
- Heavy Duty Mounting Base for Winch
- Straight End of Frame for Oilfield Bed Tail-Roller Installation
- Single, Round "Extended Life" type Halogen Headlamps
- Dual, Roof-Mounted Marker Lights
- Dual, Amber-Colori Revolving Beacon Lights
- Halogen type Fog Lights Mounted Under Front Bumper
- Single, Driver Operated, Halogen Spotlight mounted on Left Hand Side of Driver Cab
- Fender-Mounted, Front Turn Signals with Guards Rear Combination Type Stop / Tail
   / Turn / Back-up Lights Recessed in Rear Skirt
- "Plug-in" connection at end of the bed to attach "driver braking" warning beeper.
- Kenworth Export Severe Service Cab and Chassis Reinforcement Package for long life
- Conventional, Low Corrosion Cab with aluminium, Steel and Fiberglass Construction
- Sheet-metal Hood with Steel Butterfly Top Panels and Fiberglass "Drop-in" Side Panels
- Wide Steel Sheet-metal Fenders with Non-Skid Paint on top side
- Steering Column with Tilt and Telescopic Adjustment Capability
- Driver Cab Heater & Air Conditioner system for high ambient temperature operations
- Kenworth Ergonomic Design Dash with Gauges that have Primary Metric Readings

  √ Kenworth standard Vehicle Operation Warning Light Bar
- Electronic (KPH reading) Speedometer with Trip Meter
- Electronic Tachometer with Integral Engine Hour-meter
- Front Axle Engagement Warning Light
- Dual Air Reservoir Pressure Gauges with Integral Warning Light
- Air Application Gauge
- Air Filter Restriction Gauge
- Engine Oil Pressure with Integral Warning Light
- Engine Coolant Temperature with Integral Warning Light
- Transmission Oil Pressure Gauge and Oil Temperature Gauge
- Fuel Tank Level Gauge
- Electrical Voltmeter with Integral Warning Light
- Electrical Ammeter with Integral Warning Light

End of Specification.
Soft copy in USB .
<ul> <li>Three sets, comprising an Illustrated Parts hard copy CatLog &amp; Maintenance (Workshop) Manual</li> </ul>
Black
Standard, Imron Brand 2-stage Base/Clear, One Solid colour Cab Paint Scheme, with
Manual Type, Tire Inflation Kit with 50-foot Hose, Gauge, and large-Bore Chuck
Full Truck / Tractor Air and Electric Kit for air and electric power supply to trailers
Midland Automatic Moisture Ejection Valve for easier maintenance requirements
Bendix High-Capacity Air Dryer for severe service, high humidity operations
<ul> <li>Exterior Sun visor for enhanced driver visibility, comfort, and safety</li> <li>Electric, Two-Speed, plus Intermittent Speed, Windshield Wipers</li> </ul>
17-inch X 36-inch Sliding Rear Cab Window plus Corner Post Windows in Cab  State of the Sta
Dual, Wide-Load Width Mirror Brackets with 7-inch X 16-inch Mirrors  17:
Dual, Air Horns on Roof & Single Electric Horn Mounted Behind the Vee-Style Grill
Single, Convex Mirror above Right Hand Door for enhanced driver visibility & safety
View Window in Right Hand Door for enhanced driver visibility and safety
Kenworth Daylight type Door for enhanced driver visibility and safety
Grab Handles on Left- and Right-Hand Sides of the Cab to assist safe entry and exit.
Arabic Language Nameplates that are Shipped Loose for Local Installation
AM/FM Radio. Includes Wiring, Speakers, and Antenna
Three Point type Seat Belts for one Driver and one Passenger
Material
Kenworth Toolbox, Intermediate back Passenger Seat covered with Mordura
Material
Kenworth Aircushion, Intermediate back, Driver Seat covered with Mordura
Kenworth "Splendour" Cab Interior with Slate Gray colour